

# RHINO 660 UTILITY ATV

Rhino 660 Utility ATV Engine

Rhino 660 Utility ATV

Dimensions / Other

<b>Bore x Stroke (mm)</b>	:	100 x 84mm	<b>Overall Dimensions (L x W x H)</b>	:	2 885 x 1 385 x 1 853mm
<b>Compression Ratio</b>	:	9.1 : 1	<b>Seat Height</b>	:	N/A
<b>Carburetion</b>	:	BSR42	<b>Wheelbase</b>	:	1 910mm
<b>Starting</b>	:	Electric	<b>Ground Clearance</b>	:	280mm
<b>Transmission</b>	:	Ultramatic V-belt with all-wheel engine braking	<b>Dry Weight</b>	:	479kg
<b>Final Drive</b>	:	On-Command push button 2WD, 4WD locked 4WD, Shaft	<b>Fuel Capacity</b>	:	28 Liters
<b>Displacement</b>	:	660cc			
<b>Ignition</b>	:	DC-CDi			
<b>Front Suspension</b>	:	Independent double wishbone, 185mm 5-way			
<b>Rear Suspension</b>	:	Independent double wishbone, 185mm 5 way			
<b>Brakes Front</b>	:	Hydraulic disc, Twin Piston X 2			
<b>Brakes Back</b>	:	Hydraulic Disc, Shift Mounted X 1			
<b>Front Tyre</b>	:	AT25x8-12 NHS			
<b>Rear Tyre</b>	:	AT25x10-12 NHS			

# RHINO 700 UTILITY ATV

Rhino 700 Utility			Rhino 700 Utility		
			Dimensions / Other		
<b>Bore x Stroke (mm)</b>	:	102 mm x 84 mm	<b>Overall Dimensions (L x W x H)</b>	:	2885 mm x 1385 mm x 1853 mm
<b>Compression Ratio</b>	:	9.2 : 1	<b>Seat Height</b>	:	N/A
<b>Carburetion</b>	:	Single Mikuni 41 mm	<b>Wheelbase</b>	:	1910 mm
<b>Starting</b>	:	Electric	<b>Ground Clearance</b>	:	280 mm
<b>Transmission</b>	:	Ultramatic® V-belt automatic with engine breaking hi/lo/rev	<b>Dry Weight</b>	:	510 kg
<b>Final Drive</b>	:	Shaft	<b>Fuel Capacity</b>	:	30 Litres
<b>Displacement</b>	:	686 cc			
<b>Ignition</b>	:	TCI			
<b>Front Suspension</b>	:	Independent Double Wishbone, 185 mm of wheel travel, 5-way preload adjustment			
<b>Rear Suspension</b>	:	Independent Double Wishbone, 185 mm of wheel travel, 5-way preload adjustment			
<b>Brakes Front</b>	:	Dual Hydraulic Disc			
<b>Brakes Back</b>	:	Dual Hydraulic Disc / Shaft mounted parking brake			
<b>Front Tyre</b>	:	AT25 x 8-12			
<b>Rear Tyre</b>	:	AT25 x 10-12			